

SPOT

Satellite GPS Messenger

Includes all the same functionality as before — now in a smaller, more feature-rich form factor.

- 30% Smaller
- 30% Lighter
- Faster GPS Acquisition

New Features / Enhancements:

- Advanced GPS
- GPS acquisition light
- Custom message button
- Enhanced antenna performance
- Dedicated tracking button
- Improved tracking performance
- Safety covers over S.O.S. and Help buttons
- Replaceable button covers
- Illuminated buttons
- Message sent indicator light
- · Includes armband case
- Recyclable packaging





Orange

Silver

MSRP **\$169.95**

Contact Info:







FEATURES

SOS: Emergency assistance request sent with your GPS location to GEOS every 5 min until batteries die or until cancelled



Help/SPOT Assist: Request help from friends and family every 5 min for 1 hour. Up to 10 contacts -

phone & email

Check In: Lets contacts know where you are and that you're okay. Attempts to send three messages to help ensure successful transmission. Up to 10 contacts-phone & email. Contacts will receive only 1 message



Custom Message: Create custom non-urgent message to send to friends and family

Track Progress: Acquires your GPS location every 10 minutes for 24 hours. Sends each location one time. Previous 2 track points sent with current track point helping ensure consistent recording of movements

Emergency Response Center: GEOS is operational 7 days/wk. 365 days a year, operating out of Houston, Texas (2 addl. backup locations)

History Review: Review all Check In, Track, Alert SOS, and Help locations via findmespot.com using Google Maps for up to 30 days

Shared Page: You can share messages and locations with others via a personal shared page (optional password protection) or SPOT Adventures account at www.spotadventures.com. Live data viewing up to 7 days, data storage in account up to 30 days. Can have up to 10 shared pages

Button Covers: Prevent accidental activation of SOS or Help features

GPS Signal Indicator: Visual LED status of GPS signal acquired

Message Sent Indicator: Visual LED status of message sent

Security: Data protection via the latest techniques. 3rd party penetration testing two times/yr by Plynt.com VeriSign certificate (Share Page & Login Site) Latest security patches updated quarterly Network has firewalls and port scanning

Removable Case: Flexible attachment solution providing Arm Band, Carabiner & Car Dash attachment. Reflective material

International Communication: Universally accepted icons to communicate button features

Color: Matte orange and gloss silver

Replaceable Button Covers: One set included

TECHNOLOGY

GPS Satellites:

21 ft (6.4 m) location accuracy

LEO Satellites:

1610-1620 MHz L-band frequency

Satellite Speed:

17,000 MPH

114 min. to circle earth

Distance:

876 miles (1414 km) above Earth Altitude (twenty times closer than fixed satellites) Requires less power Less power usage allows more frequent updates Less power usage allows other value-added uses

Visibility:

1 to 4 at any one time More satellites for SOS detection than anyone More satellites means signal can be detected sooner

Angle of Detection:

Constantly changing, helps in dense coverage

Beam Coverage:

Overlaps, increased detection probability

Movement:

Constantly, 8 planes 52° inclination

Communication:

If no GPS fix, SPOT sends distress signal without GPS position to emergency response center Previous Check In or Track Mode data provides fast and close proximity

SPECIFICATIONS

Export Data:

CSV (spreadsheet), KML (Google Earth™), GPX (GPS data)

Certifications:

FCC, IC, WEEE: Outside of Case SAR, RoHS, CE1313: Inside Case

Additional Specs:

-Size: 3.7" x 2.6" x 1.0" (9.4 x 6.6 x 2.5 cm)

-Wt: 5.2 oz (147.4 g)

-SOS Transmit: 5 min. intervals until batteries die, 1350

transmissions on fresh battery

-Help/SPOT Assist Transmit: 5 min. intervals for 1 hr

-Check In/Custom Message Transmit: three times within 20 min. only posts one

-GPS Lat. Lon. datum format: WGS-84

Operating Environment:

Temperature: $-22^{\circ}F$ to $+140^{\circ}F$ ($-30^{\circ}C$ to $+60^{\circ}C$) Altitude: -328 ft to 21,325 ft (-100 m to +6500 m)

Humidity: MIL-STD-810F Method 507.4 95% to 100% condensing Salt Fog: Per MIL-STD 810E Method 509.3, 5% NaCl, 95% distilled water

Vibration: Per SAE J1455, Random, 20 Hz to 2000 Hz, 0.04g_/Hz

Water Proof: 16.4 ft (5 m) submersion for 1 hour

Buoyant: Yes

Power:

Batteries: 3 AAA lithium Transmission Power: 0.16 Watts Standby mode: 110 days

LEDs:

On/Off OK/Check Message Track SOS Heln **GPS** Acquired

Message Sent